



中效大折景过滤器 Rigid Cell



性能 Capacity

※外框: 铝框、镀锌框

Frame: Aluminum, galvanized steel

※滤材: 化学纤维(人纤)

Media: Meltblown PP

※效率(Efficiency): ASHRAE 45%, 65%, 85%, 95%

※标准(Standard): EN779 F5, F6, F7, F8

使用环境 Operating Conditions

※最高温度70℃ (Temperature: ≤70℃)

※最高湿度90%RH (Humidity: ≤90%RH)

技术参数 Technical Parameters

宽*高*深 W*H*D (Inch)	宽*高*深 W*H*D (Mm)	滤材面积 Area (M²)	效率 Efficiency	风量 Airflow (CMH)	初压损 Initial Pressure (Pa)	风量 Airflow (CMH)	初压损 Initial Pressure (Pa)※
12*24*6	289*593*150	1. 27	F5	925	50	1230	70
			F6		60		80
			F7		70		95
			F8		80		110
24*24*6	593*593*150	2. 53	F5	1900	50	2520	70
			F6		60		80
			F7		70		95
			F8		80		110
12*24*12	289*593*292	2. 73	F5	1230	52	1650	70
			F6		60		80
			F7		70		95
			F8		82		110
24*24*12	593*593*292	5. 51	F5	2520	52	3400	70
			F6		60		80
			F7		70		95
			F8		82		110
建议终压损: 250Pa Recommended final pressure: 250Pa							

※Pressure range ±15%.

特殊尺寸及规格可依客户要求制作。

Different sizes and specifications are available

应用场所 Applications

一般应用于中央通风系统的中效和亚高效过滤。特别是使用时, 可用以保护高效过滤器, 延长其使用寿命。作为高效过滤器的预过滤器。适用于大风量的通风空调系统。

Rigid cell filters are used for secondary filtration in central ventilation systems, particularly to protect and extend the life of HEPA filters. They are suitable for use in ventilation and air conditioning systems of various airflows.

昆山富雷克环保净化科技有限公司(中国)

Kunshan Fleco Filtration Co., Ltd.

地址: 中国江苏省昆山市环庆路1893-1号 邮编: 215316

Address: 1893-1 Huanqing Road, Kunshan, Jiangsu, China Zip: 215316

电话/TEL: 86-(0)512-57759300 传真/FAX: 86-(0)512-57759336

邮箱/E-mail: sales@flecofiltration.com.cn 网页/Website: www.flecofiltration.com.cn