




Synthetic Pocket Filter



Capacity

- ※Frame: Galvanized steel, extruded aluminum, plastic
- ※Header: 20mm, 25mm
- ※Media: Meltblown PP
- ※Efficiency: ASHRAE 45%、65%、85%、95%
- ※Standard: EN779 F5、F6、F7、F8
- ※High-loft, layered, meltblown synthetic media improves performance
- ※Ultrasonically-welded pocket spacers and edges
- ※Available with antimicrobial

Operating Conditions

- ※Temperature: ≤70°C
- ※Humidity: ≤90%RH

Technical Parameters

W*H*D (mm)	Pockets	Area (m ²)	Efficiency	Airflow (CMH)	Initial Pressure (Pa)	Airflow (CMH)	Initial Pressure (Pa)※
592*592*600	8	6.40	F5	2540	30	3800	45
			F6		40		60
			F7		75		110
			F8		85		130
592*592*600	6	4.97	F5	2540	35	3800	50
			F6		50		75
			F7		80		120
			F8		90		135
490*592*600	5	4.13	F5	2100	35	3140	50
			F6		50		75
			F7		80		120
			F8		90		135
287*592*600	3	2.46	F5	1240	35	1860	50
			F6		45		75
			F7		80		120
			F8		90		135
592*592*560	8	6.40	F5	2540	35	3800	40
			F6		45		65
			F7		80		120
			F8		95		140
592*592*560	6	4.97	F5	2540	40	3800	55
			F6		55		80
			F7		85		130
			F8		95		145
287*592*560	3	2.46	F5	1240	40	1860	55
			F6		55		80
			F7		85		130
			F8		95		145

Recommended final pressure: 450Pa

※Pressure range ±15%.

Different sizes and specifications are available

Applications

Pocket filters have widespread application in central air conditioning ventilation systems, pharmaceuticals, hospitals, electronics, food processing, etc. They can also be used for secondary filtration to reduce load and prolong service life of high-efficiency air filtration systems. Pocket filters have high dust holding capacity and high air speed due to their large surface area. Therefore, they are the optimal medium-efficiency filter structure for secondary filtration.

Fleco Int'l Corp.

Kunshan Fleco Filtration Co., Ltd.

Address: 1893-1 Huanqing Road, Kunshan, Jiangsu, China Zip: 215316

TEL: 86-(0) 512-57759300 FAX: 86-(0) 512-57759336

E-mail: sales@flecofiltration.com.cn Website: www.flecofiltration.com.cn